

Manufacturer:

OGNIOCHRON S.A.

ul. Przemysłowa 42, 34-120 Andrychów, Poland
tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

www.ogniochron.eu

ogniochron

Application

Applicable in paint shops, power industry, industrial halls and everywhere where usage of extinguishing powders is not recommended due to presence of devices sensitive to dust and impurities. The extinguisher does not leave any remains after application.



Basic features

- Easy and ergonomic operation.
- Long hose with a snow horn at the end makes extinguishing easier.
- New generation of light, steel cylinder.
- Economical maintenance and service.
- Valve equipped with bursting disc.
- Construction of the valve enables temporary interruption of extinguishing.
- For extinguishing of fire type C.
- Cylinder of extinguisher covered with polyester paint, resistant to UV radiation.


Quality and safety

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of European Standard EN3 and Safety Directive PED 2014/68/UE.



Technical data

Extinguishing efficiency	89B
Weight of extinguishing agent	5 kg
Operation time	min. 9 s
Cylinder test pressure	315 bar
Operating temperature	-30 °C/+60 °C
Total weight	~14 kg
Fire under voltage	1000 V
Total height (A)	700 mm
Cylinder diameter (B)	136 mm



Carbon dioxide extinguisher

GS-5x B/MP

